


**POMPE AD INGRANAGGI GAMMA PRODOTTO**  
**GEAR PUMPS PRODUCT RANGE**


GRUPPO GROUP 1SP	CILINDRATA DISPLACEMENT		VELOCITÀ MAX MAX SPEED	PORTATA MAX MAX FLOW		VELOCITÀ MIN MIN SPEED	PORTATA MIN MIN FLOW		RENDIMENTO VOLUMETRICO MIN. MIN. VOLUMETRIC EFFICIENCY
	cm <sup>3</sup> /giro	in <sup>3</sup> /rev	giri/min - rpm	l/min	Gal/min	giri/min - rpm	l/min	Gal/min	%
<b>1SP 009</b>	0.89	0.05	6000	5.3	1.40	600	0.49	0.13	92*
<b>1SP 012</b>	1.18	0.07	6000	7.1	1.88	600	0.65	0.17	92*
<b>1SP 016</b>	1.6	0.10	6000	9.6	2.54	400	0.61	0.16	95*
<b>1SP 020</b>	2.0	0.12	5500	11	2.91	400	0.76	0.20	95*
<b>1SP 025</b>	2.5	0.15	5000	12.5	3.30	400	0.95	0.25	95*
<b>1SP 032</b>	3.2	0.20	4500	14.4	3.80	400	1.21	0.32	95*
<b>1SP 037</b>	3.7	0.23	4000	14.8	3.91	400	1.40	0.37	95*
<b>1SP 042</b>	4.2	0.26	3500	14.7	3.88	400	1.60	0.42	95*
<b>1SP 050</b>	5.0	0.31	3000	15	3.96	400	1.90	0.50	95*
<b>1SP 063</b>	6.3	0.38	2700	17	4.49	400	2.39	0.63	95*
<b>1SP 078</b>	7.76	0.47	2500	19.4	5.13	400	2.95	0.78	95*
<b>1SP 098</b>	9.78	0.60	2000	19.6	5.18	400	3.71	0.98	95*

\* = Valori medi rilevati in fase di collaudo a 1500 giri/min. *Average values recorded during the testing at 1500 rpm.*


## FLANGE - FLANGES

**EUR**



pagina/page 18

**SAEAA**



pagina/page 19

**MC32**


pagina/page 20

**E32BX - E32BC**


pagina/page 21

**E32CX - E32CC**


pagina/page 23